

0009488644 - Drawing available
 WPI ACC NO: 1999-430684/199936
 Laminate, provides optical orientation
 Patent Assignee: 3M INNOVATIVE PROPERTIES (MINN); 3M INNOVATIVE PROPERTIES
 CO (MINN); MINNESOTA MINING & MFG CO (MINN)
 Inventor: ALLUN R C; ALLEN R C; CONDO P D; MERRILL W W; MERRILL W; MERRILL W
 W; NEVITT T J; TABAR R J; ALAN R C; CONDE P D; MERYL W W; NEVITTE T J;
 TABBAR R J

Patent Family (17 patents, 82 countries)

Patent Number	Kind	Date	Application Number	Kind	Date	Update
WO 1999036812	A1	19990722	WO 1998US26331	A	19981210	199936 B
AU 199917227	A	19990802	AU 199917227	A	19981210	199954 E
EP 1047965	A1	20001102	EP 1998962061	A	19981210	200056 E
			WO 1998US26331	A	19981210	
US 6179948	B1	20010130	US 19986455	A	19980113	200127 E
CN 1285923	A	20010228	CN 1998813054	A	19981210	200131 E
KR 2001034091	A	20010425	KR 2000707701	A	20000712	200164 E
BR 199814584	A	20011023	BR 199814584	A	19981210	200172 E
			WO 1998US26331	A	19981210	
US 6329046	B1	20011211	US 19986455	A	19980113	200204 E
			US 1999419947	A	19991018	
JP 2003526802	W	20030909	WO 1998US26331	A	19981210	200360 E
			JP 2000540466	A	19981210	
CN 1525198	A	20040901	CN 1998813054	A	19981210	200478 E
			CN 200310119938	A	19981210	
EP 1047965	B1	20050413	EP 1998962061	A	19981210	200525 E
			WO 1998US26331	A	19981210	
DE 69829780	E	20050519	DE 69829780	A	19981210	200536 E
			EP 1998962061	A	19981210	
			WO 1998US26331	A	19981210	
CN 1169003	C	20040929	CN 1998813054	A	19981210	200615 E
JP 2006099139	A	20060413	JP 2000540466	A	19981210	200626 E
			JP 2005357973	A	20051212	
DE 69829780	T2	20060427	DE 69829780	A	19981210	200629 E
			EP 1998962061	A	19981210	
			WO 1998US26331	A	19981210	
CN 1268947	C	20060809	CN 200310119938	A	19981210	200703 E
KR 605431	B1	20060728	WO 1998US26331	A	19981210	200728 E
			KR 2003716183	A	20031210	

Priority Applications (no., kind, date): US 19986455 A 19980113; US
 19986455 A 19980113; US 1999419947 A 19991018

Alerting Abstract WO A1

NOVELTY - Optical film is formed by processing a film (111) having two materials (113, 115) with respect to first and second in-plane axes (X, Y) of the film under conditions which induce optical orientation in the first material which differ substantially in the two directions such that the refractive index of the second material matches the refractive index of the first material along one of the two axes.

DESCRIPTION - INDEPENDENT CLAIMS are also included for the following:

1. an optical film comprising two co-extruded materials one of which has an orientation along each of first and second in-plane axes, and the

other having orientation along only the first in-plane axis, such that the refractive index (RI) of the two materials along one of the two axes is the same and the absolute value of the difference between the two materials along the other axis divided by the average RI index of the two materials is greater than 0.06;

2. making an optical film comprising applying to a film of a first material optically interfaced with a second material having a different visco-elasticity characteristic, a draw in a first direction to induce optical orientation of the second material, and processing the film to produce optical orientation of both materials in a second direction;
3. making a polarising film using a multilayer film having two optically interfaced layers of birefringent material which have different isotropic RI's, drawing the film in one in-plane axis such that the RI of the first layer along the two in-plane axes, and a third axis orthogonal to the in-plane axes, and the RI of the second layer along the second in-plane axis are unchanged, while the RI of the second layer along the first in-plane axis is changed to be equal the RI of the first layer along the same axis, and drawing the multilayer film in the direction of the second in-plane axis such that the RI of the two layers along the third axis are equal; and
4. an optical polarising film comprising a blend of a disperse phase of a first polymeric material optically interfaced with a continuous phase of a second polymeric material, the second material having a molecular orientation which is strong along a first axis and weak along a second axis of the film, and the two films having RI's along one of the axes matched so as to transmit light of a first polarisation with RI's along the other axis so different as to reflect light of a second polarisation.

USE - Used in optical films, particularly polarising films.

ADVANTAGE - Provides improved optical performance increased resistance to fracture or tear, enhanced dimensional stability etc.

DESCRIPTION OF DRAWINGS - The figure shows the optical film.

111 film laminate

113, 115 first and second material

X, Y first and second in-plane axes

2 thickness direction axis